

Technical specifications

Model	Portascanner® WATERTIGHT PLUS
Receiver Unit	Dimensions: 85 x 229 x 35 mm (L x H x W)
	Weight: 400 g (14.11 oz)
	Power: 1x PP3 9V battery
	Battery Life: 10 hours continuous use (with low battery indication)
	Readings: Visual (via LCD display and graph) or audible (via external headphones)
	Display: Membrane control operated, LCD back-lit Display measuring 55 x 28 mm
Generator Unit	Dimensions: 147 x 89 x 54 mm (L x H x W)
	Weight: 400 g (14.11 oz)
	Output: Triple 40kHz transducers, multi-directional
	Power: 3 x PP3 9V battery
	Battery Life: 12 hours continuous use
Receiver Wand	Type: Flexible Sensor Wand
	Total Length: 900mm (35.43 inches)
	Rod Diameter: 25mm (0.98 inches)
	Extension parts available for longer length
	Connected by BNC to 1.8m length co-axial cable
General	Operating Temperature: -20 ~ +70°C (-4 F +158 F)
	Enclosure IP Rating: IP 67
	Smallest detectable leak: 0.06 ±0.02 mm hole size
	Operating Modes: Linear/Decibel/OHV modes
	Approvals: Full ABS Type Approval; Classification Society Accepted- RINA; UKCA CE; ExVeritas ISO 9001
	Certificate: Manufactured in England with ISO 14001 and ISO 9001:2015 registered company
	Technical Support: Lifetime of the unit