

Pocket carat balances KERN CM-C · TGD



**KERN CM-C**

Pocket balance with carat display – ideal for jewellers



**KERN TGD**

Compact pocket carat balance for precision weighing of jewellery and precious stones



STANDARD

- CAL EXT
- UNIT
- BATT
- 1 DAY

STANDARD

- CAL EXT
- UNIT
- BATT
- 1 DAY

OPTION

- DAkkS +3 DAYS

OPTION

- DAkkS +3 DAYS

- Hard case cover as protection against pressure and dust
- Adjusting weight standard
- Draft shield against air movements standard
- Weighing pan standard

- Simple and convenient 4-key operation
- Can be switched over from g to ct, gn, dwt, ozt, oz at the touch of a key
- Innovative touchscreen: Large touch-sensitive, backlit touch display with very good contrast for easy operation and convenient reading
- Hard case cover as protection against pressure and dust
- Stainless steel weighing plate, which makes cleaning easy and hygienic
- Weighing pan standard
- Powder scale with Grain division (gn), ideal for sport shooters, reloaders etc. for self-filling cartridge cases
- USB cable for power supply as standard
- **1** Delivered in appealing packaging
- **Note:** The models are only delivered in a set of 5 units. That means the prices given in the table refer to a delivery of 5 units. Cannot be delivered individually. The calibration prices given here refer to calibration of a single balance

**Tip:** KERN pocket scales are also ideal as a customer gift or for personalised marketing and sales campaigns. We are happy to print your logo on the cover, the lid or the packaging, up from 100 pieces. Please inquire details

KERN	CM 50-C2N*	TGD 50-3CS05
<b>Weighing capacity [Max] g</b>	10 g   50 ct	50 g   250 ct
<b>Readability [d]</b>	0,002 g   0,01 ct	0,001 g   0,005 ct
<b>LCD display</b>	digit height 9 mm	backlit, digit height 12 mm
<b>Dimensions of weighing plate</b>	W×D 50×40 mm	ø 65 mm
<b>Overall dimensions</b>	W×D×H 85×130×25 mm	W×D×H 96×149×36 mm
<b>Power supply</b>	Batteries included, 2×1,5 V AAA, AUTO-OFF function to preserve battery life, can be switched off, operating time up to 30 h	Batteries included, 4×1,5 V AAA, operating time up to 150 h without backlight
<b>Net weight</b>	200 g	
<b>Permissible ambient temperature</b>	5 °C/35 °C	5 °C/35 °C
<b>Option DAkkS Calibr. Certificate</b>	963-127	

**1** \* ONLY WHILE STOCKS LAST!