BG30 GAS DETECTOR

Quick and easy detection of gas leaks





A FEW PRACTICAL BENEFITS:

Gas warning device and gas detector in one device

Visual and acoustic alarm signal

Alarm frequency in relation to gas concentration

Individual calibration via infinitely variable sensitivity control

Easy, one-hand operation

Optimum value-for-money ratio

Semi-rigid gooseneck probe of 40 cm length for the examination in poorly accessible locations



The BG30 is a must-have when you combustible gas is stored or used at home, on the camping site or boat. For safty, regularly check your camping gas cartridges, LPG containers or gas soldering irons for tightness.

The BG30 is a versatile measuring device i.a. for the detection of gas leaks on pipelines or fittings.

With 10 % LEL the BG30 is more sensitive than the alarm threshold stipulated in many standards or regulations. LEL stands for lower explosive limit and defines the minimum concentration of gas on the air, that enables an explosion.

The BG30 reliably detects natural gas, methane, ethane, propane, butane, acetone, alcohol, ammonia, petrol, LPG, turbine fuel, hydrogen sulphide, industrial solvents, paint thinners and other combustible gases

Technical date		BG30 GAS DETECTOR
Article number		3.510.205.064
Combustible gases	Accuracy	50 ppm
	Alarm range	10% - 40% LEL
	Warm-up time	Around 60 s
Power Supply	Battery	3 x 1.5 V, C
Temperature	Operation range	0 - 50°C
	Storage range	-30 -60 °C
Demensions		221 x 24 x 72mm
Weight		520 g

PROMAT (HK) Limited 寶時(香港)有限公司





