<u>Humidity | Humidity loggers</u>

Multimeasure – Humidity –Humidity loggers

6 Inch Temperature & Humidity Chart

movement, and a menu of features to best suit your applications.

Our 6" (152mm) line of humidity chart recorders feature a sleek look and feel, precision pen



## 6" Chart (152mm) User selectable recording times and temperature ranges AC power with battery backup Model TH621 TH622 Model TH621 TH622 Bescription 6" (152mm) Temperature & Humidity Chart 6" (152mm) Temperature & Humidity Chart

Model	TH621	TH622	TH623
Description	6" (152mm) Temperature & Humidity Chart Recorder	6" (152mm) Temperature & Humidity Chart Recorder with Display	6" (152mm) Temperature & Humidity Chart Recorder with Display, Probe and Alarm
Remote Probe			~
Display		V	~
Alarm			~
Temperature Range	32 to 100°F (0 to 50°C)	32 to 100°F (0 to 50°C)	32 to 100°F (0 to 50°C) 32 to 185°F (0 to 85°C)
Temperature Accuracy	±1.8°F from 32 to 120°F (±1°C from 0 to 50°C)	±1.8°F from 32 to 120°F (±1°C from 0 to 50°C)	±1.8°F from 32 to 120°F (±1°C from 0 to 50°C)
Humidity Range	0-95% non-condensing	0-95% non-condensing	0-95% non-condensing
Humidity Accuracy	±2% RH from 0 to 60% ±3% RH from 60 to 95%	±2% RH from 0 to 60% ±3% RH from 60 to 95%	±2% RH from 0 to 60% ±3% RH from 60 to 95%

## PROMAT (HK) Limited

TEL: 2661 2392 FAX: 2661 2086 Email: info@promat.hk Address: 901 New Trend Center, 704 Prince Edward Road East, Sanpokong, Kowloon, Hong Kong