

Promat (HK) Ltd

901 New Trend Centre, 704 Prince Edward Road East, San Po Kong, Kowloon, Hong Kong

寶時(香港)有限公司

香港九龍新蒲崗太子道東 704 號新時代商業中心 901 室

Tel.: (852) 2661 2392 Fax: (852) 2661 2086 e-mail: info@promat.hk [http:// www.promat.hk](http://www.promat.hk)



PROMAT - Curing Tank

Model: PC-016

Apparatus of curing concrete

Galvanizing Curing Tank to CS1:2010

PC-016	Internal Size:	1.65(L) x 0.86(W) x 0.51(H)m
PC-016A	Internal Size:	2.2(L) x 1.2(W) x 0.9(H)m
PC-016B	Internal Size:	1.04(L) x 1.04(W) x 0.605(H)m
PC-016C	Internal Size:	0.6(L) x 0.8(W) x 0.6(H)m
PC-016D	Internal Size:	0.6(L) x 1.8(W) x 0.6(H)m
PC-016E	Internal Size:	2.4(L) x 1.2(W) x 0.9(H)m
PC-016F	Internal Size:	2.0(L) x 1.2(W) x 0.9(H)m
PC-016G	Internal Size:	1.8(L) x 1.2(W) x 0.9(H)m

Features and Benefits

- Galvanized steel curing tank
- Flexible size on request
- Lockable Lid and pad lock
- Submerged water pump for water circulation
- Drainage valve and overflow system
- Thermostatically controlled heating system
- Racks and mesh
- Stands
- Max/min water resistance thermometer (optional)
- Temperature chart recorder (optional)
- Infrared thermometer (optional)
- Plastic cube separator 23" x 15" (optional)
- HOKLAS Calibration certificate (optional)
- Complies with CS1:2010



Max/min Water resistance thermometer



Temperature chart recorder



Infrared thermometer

Technical Specification

Temperature Limit: 27°C +/- 1°C

Electrical Input: [120v/1ph, 208v/1ph, 230v/1ph, 208v/3ph, 230v/3ph]

Electrical Output: 2000W, 3000W

Pump: 4500 L/Hr, 0.6 Bar

(P.S. Please contact us for different size required.)