

Monitor with Confidence TEL 604 540 1100 info@rstinstruments.com www.rstinstruments.com

Z

PRODUCT CATEGORY:

INCLINOMETERS + TILT SENSORS

RST Instruments Ltd. 11545 Kingston St., Maple Ridge, BC V2X 0Z5 Canada





## TILT SENSOR SPECIFICATIONS

ITEM	DESCRIPTION
Range	±15°
Resolution	$\pm 2 \text{ arc sec.} (\pm 0.0006^{\circ}) (0.01 \text{ mm/m})$
Non-linearity	$\pm 0.0125\%$ F.S. ( $\pm 0.002^{\circ}$ ) (0.03 mm/m)
Repeatability	$\pm 0.0125\%$ F.S. ( $\pm 0.002^{\circ}$ ) (0.03 mm/m)
Sensor	MEMS (Micro-Electro-Mechanical Systems) Accelerometer
Material	Stainless steel / Aluminum NEMA 4X (IP-65) weather proof enclosure
Weight	10.38 lbs (4.710 kg)

TILT PLATE SPECIFICATIONS		
ITEM	SPECIFICATION	
Material	316 stainless steel	
Dimensions	5.5 in. OD x 2.5 ID x 0.95 (140 x 63 x 14 mm) 4 pegs equally spaced on 4 in. (102 mm) dia.	
Weight	1.7 lbs (0.77 kg)	
Installation	Epoxy or mechanical 4 x ¼ mounting holes on 4 in. (102 mm) dia.	

## **Portable Tilt Meter**

The RST Portable Tilt Meter utilizes a MEMS tilt meter to measure tilt in either one or two axial planes perpendicular the surface of the base plate. The output is a digital output and is directly proportional to the sine of angle of tilt. In the horizontal position the DC output is zero. Portable MEMS Tilt Meters require placing the tilt meter in a reproducible position on a reference plate attached to the surface being monitored. It is designed for applications where a large number of measuring points are to be observed.

Portable MEMS Tilt Meter systems consist of the tilt meter, stainless steel tilt plates and the Field PC<sup>2</sup>. Tilt plates are bolted or bonded to the structure to accurately, and repeatedly, locate the sensor.

> AP	PLICATIONS
Monitor	tilt of retaining and building walls.
Tilt of co	oncrete dams.
Ground	subsidence.
Building	safety along adjacent excavations.
Bridge p	piers.
Applicat	ions where the failure mode is expected to have a rotational component.
> FE	ATURES
Horizon	tal or vertical applications.
High ac	curacy and repeatability.
Readou	t units and portable sensor are lightweight and easy to use.
> BE	NEFITS
> BE	Increase Safety
~	Increase Safety

ORDERING INFO		
ITEM	PART #	
Portable MEMS Tilt Meter - Digital Output (horizontal/vertical)	ICTS0005	
Tilt Plate	ICTS0010	
Ultra-Rugged Field PC <sup>2</sup>	IC32000-AR2-RSTS	

