

Natural Convection Oven



**One Touch
Door Lid**



Certified

Feature

Digital PID Control

membrane type touch keypad provides precision temperature control, timer, alarm, auto-tuning.

Tempered Safety Glass Window

for easy sample view without door opening

Dust-Free Gravity-Flow Convection

gentle drying up to 250°C max

Safety and Convenience

over temperature and current protection, leakage breaker ensure user safety and adjustable sliding rack

MODEL		LDO-030N	LDO-080N	LDO-150N	LDO-250N
Dimensions (WxDxHmm)	Inner	350 x 320 x 320	400 x 400 x 500	500 x 500 x 600	600 x 600 x 700
	Outer	500 x 485 x 695	550 x 610 x 850	650 x 710 x 950	750 x 810 x 1050
Capacity		32ℓ	80ℓ	150ℓ	252ℓ
Temperature	Range	Ambient +10°C to 250°C			
	Set Accuracy	±1.0°C			
	Uniformity	±5.0°C at 120°C			
Heater		1kW	1.5kW	2kW	3kW
Display		LED 4 Digits Display			
Controller		PID Multi-Function Controller, Alarm, Auto tuning			
Timer		99min 59sec. / 99hr 59 min / 99days 23hours / Continuous Selectable			
Material	Interior	Stainless Steel			
	Exterior	Epoxy powder coated steel			
Shelves		2EA			3EA
Door		Tempered Glass Window with Silicone Packing (Model without Glass Door Available)			
Insulation		Ceramic and Glass Wool			
Safety		Over Heat Protector Over Current & Leakage Breaker			
Electric Supply		110V, 60Hz or 220V, 50/60Hz			



Custom made order is available
Specifications can be changed without prior notice for quality improvement.

PROMAT (HK) Limited 寶時 (香港) 有限公司

☎ : 2661 2392 ☎ : 5196 8860 ✉ : info@promat.hk 🌐 : http://www.promat.hk

