



PROMAT
Your Solution To Testing Instrument

ZRS 6060 Retroreflectometer

- New generation of ergonomic retroreflectometer for determination of night visibility (coefficient of retroreflection R_A and R') of traffic signs, safety garments and other reflexive materials with measurement of three different observation angles at the same time
- The very first retroreflectometer with LED illumination system and with a 3.5" high resolution colour touchscreen with adjustable display inclination for excellent visibility under all light conditions also in bright sunlight
- For all kinds of retroreflective materials and colours with automatic colour indication
- Continuously updated average value; each single measurement is stored additionally
- Measurements can be evaluated with the included mapping and data analysis software "Mapping-Tools"
- Easy to operate with polyglot menu navigation
- Sturdy construction and ergonomic design
- Factory calibration traceable to the independent accreditation body METAS, Switzerland. The certificate of calibration is included in the standard delivery

ZRS 6060 Retroflektometer

- Ergonomisches Retroflektometer der neusten Generation zur Ermittlung der Nachtsichtbarkeit (spezifischer Rückstrahlwert R_A bzw. R') von Verkehrszeichen, Warnkleidung und anderen Reflexstoffen mit gleichzeitiger Messung aus drei verschiedenen Beobachtungswinkeln
- Das weltweit erste Retroflektometer mit LED-Beleuchtungssystem und farbigem, hochauflösendem 3.5" Touchscreen mit verstellbarer Neigung, gut erkennbar unter allen Lichtverhältnissen, auch bei Sonnenlichteinstrahlung
- Für alle Arten und Farben von retroflektierenden Materialien, mit automatischer Farberkennung
- Laufende Durchschnittsberechnung; zusätzlich wird jeder Einzelwert gespeichert
- Messungen können mit der inbegriffenen Karten- und Auswertungssoftware "MappingTools" verwaltet werden
- Einfache Handhabung mit intuitiver, mehrsprachiger Menüführung
- Robuste Konstruktion und ergonomisches Design
- Die Werkskalibrierung ist rückführbar auf die Akkreditierungsstelle METAS, Schweiz. Das Kalibrier-Zertifikat ist im Lieferumfang enthalten

PROMAT

Your Solution To Testing Instrument

PROMAT (HK) Limited 賣時(香港)有限公司

901 New Trend Center, 704 Prince Edward Road East, SPK, Kln, HK

香港九龍新蒲崗太子道東704號新時代商業中心901室

TEL: (+852) 2661 2392

FAX: (+852) 2661 2086

Email: sales@promat.hk

http://www.promat.hk



Retroreflective materials have to fulfil performance limits to the coefficient of retroreflection R_A of traffic signs and the coefficient of retroreflection R' of safety garments and contour safety markings which are defined within international standards.

Application areas

- For road authorities, road laboratories, expert witnesses as well as manufacturers of traffic signs, license plates, contour safety markings, safety garments and their customers
- Determination of the coefficient of retroreflection R_A of traffic signs as well as the coefficient of retroreflection R' of safety garments; for all types and colours of retroreflective material
- Field and laboratory use
- Quality control („pass/fail“) by manufacturers, by customers on receipt, maintenance and decision on necessary replacement
- For inventory

Standard delivery

- | | |
|--|--|
| • 1 retroreflectometer | • 1 USB-cable for data transfer to PC / laptop |
| • 1 calibration standard / front plate | • 1 certificate of manufacturer |
| • 1 battery charger | • 1 certificate of calibration |
| • 1 mapping and data analysis software „Mapping Tools“ | • 1 shoulder strap |
| | • 1 shoulder bag |

Options

- | | |
|---|--|
| • ACC797 WAAS GPS-unit | • ACC801 bluetooth®-interface |
| • ACC802 holster | • ACC804-806, ACC868 adapters for illumination angle 20°, 30°, 40° and 45° |
| • ACC547 portable USB-printer | • ACC918 barcode reader |
| • ACC798 handle 1.2 m (47.2") | |
| • ACC799 extendable handle from 1.7 m to 3 m (66.9"-118.1") | |
| • ACC800 extendable handle from 2.2 m to 4 m (86.6"-157.5") | |

Technical specification

Versions	Illumination angle β / Anleuchtungswinkel β	Observation angle α / Beobachtungswinkel α	Application / Anwendung	Standards / Normen	Ausführungen
6060.ASTM	-4°	0.2°, 0.5°, 1°		ASTM E1709, (ASTM E1809, withdrawn / zurückgezogen 2010), ASTM E2540, MUTCD	6060.ASTM
6060.CD	5°	0.2°, 0.33°, 0.5°		DIN 67 520, EN 12899-1, EN DIN 20471	6060.CD
6060.DE		0.2°, 0.33°, 1°			6060.DE
6060.EN		0.2°, 0.33°, 2°			6060.EN
6060.CEN	5°	0.33°, 0.5°, 1°		DIN 67 520, EN 12899-1	6060.CEN
6060.A.S*	-4°	0.2°, 0.33°, 0.5°, 1°, 1.5° or / oder 2° *	depending on chosen specifications / abhängig von Auswahl		6060.A.S*
6060.C.S*	5°				6060.C.S*

* Please choose 3 observation angles α

* Bitte wählen Sie 3 Beobachtungswinkel α

Measuring area	Ø 25 mm [0.98"]	Messfläche
Measuring sensor adaption	$V[\lambda]$	Mess-Sensor-Anpassung
Measuring range	0 - 2'000 cd•lx ⁻¹ •m ⁻²	Messbereich
Measuring time	≈ 3 s	Messdauer
Memory	internal flash memory / interner Flashspeicher	Speicher
Memory size / capacity	1 GB ≈ 1'000'000 measurements / Messungen	Speichergrösse /-kapazität
Interface	Host USB (type A / Typ A), Client Mini USB (type B / Typ B)	Schnittstelle
Interface optional	Bluetooth®	Schnittstelle optional
Touchscreen display	3.5" colour TFT (LCD), LED backlight, HVGA resolution / 3.5" TFT (LCD) farbig, LED Hintergrundbeleuchtung, HVGA Auflösung	Touchscreen-Anzeige
Battery	Li-Ion-Mn 14.8 V / 6.3 Ah	Akku
Operating temperature	-10°C - +50°C (14°F - 122°F), non condensing / nicht kondensierend	Betriebstemperatur
Storage temperature	-20°C - +55°C (-4°F - +131°F)	Aufbewahrungstemperatur
Material housing	anodised aluminium / Aluminium, eloxiert	Material Gehäuse
Dimensions (LxWxH)	220 mm x 85 mm x 290 mm (8.66" x 3.35" x 11.42")	Dimensionen (LxBxH)
Weight	1.9 kg (4.19 lbs)	Gewicht
Warranty	2 years / Jahre	Gewährleistung